

Platform

- ◇ Roll-out deck extension
- ◇ Drive at full height
- ◇ Fold down handrails
- ◇ Self lock gate on platform
- ◇ Removable platform console box
- ◇ Lanyard attach points
- ◇ Full proportional drive joystick control
- ◇ Proportional lift/lower speed control
- ◇ Overload sensor

Power and Transmission

- ◇ Euro V Diesel Engine
- ◇ Swing-out battery/electrical compartment doors
- ◇ Automatic levelling hydraulic outriggers
- ◇ 4WD Drive
- ◇ Four wheel automatic brake system
- ◇ Emergency brake release

Functional Equipment & Accessories

- ◇ Emergency lowering system
- ◇ On-board diagnostic system
- ◇ Battery level indicator
- ◇ Hour meter
- ◇ Lubrication free scissor arm bushing
- ◇ Scissor maintenance bar
- ◇ Cylinder holding valve
- ◇ Horn
- ◇ Non-marking solid tyres
- ◇ Slope motion cut out
- ◇ All motion alarm
- ◇ Descent alarm
- ◇ Tie down lugs
- ◇ Tilt level sensor with audible alarm
- ◇ AC Power on the platform

Optional Accessories

- ◇ Airline to platform
- ◇ Platform work lights
- ◇ Oscillation axle
- ◇ Custom paint



Model	MPD.1218RT Diesel
Dimensions	
A – Working Height	12,00 m
B – Platform Height - Lifted	10,00 m
D – Platform Height - Lowered	2,03 m
D+C – Closed Height - Stowed handrails	2,85 m
Closed Height - Handrails folded	2,15 m
C – Handrails Height	1,10 m
ExF – Platform Dimensions	4,20 x 1,80 m
K – Extension Deck	1,50 m
G – Total Width	2,28 m
L – Total Length	4,90 m
J – Wheelbase	2,86 m
Ground Clearance - Center	30 cm
Performans	
Lift Capacity	980 kg
Extension Deck Capacity	200 kg
Maximum Occupancy	7
Rise / Lower Time	60 / 50 sec
Weight	7250 kg
Gradeability	%35
Drive Speed (Rised / Stowed)	0,8 / 2,4 km
Tyres - Solid non-marking	31*10-16
Turning Radius	5600 mm
Drive Type	4WD - Hydraulic
Brake	Hydraulic
Power	
Power Source	Diesel
Engine	Perkins 404D-22 37kW
Fuel Tank	110L
Battery	12V 110Ah

