

Platform

- ◇ Roll-out deck extension
- ◇ Drive at full height
- ◇ Fold down handrails
- ◇ Self lock gate on platform
- ◇ Removable platform console box
- ◇ Lanyard attach points
- ◇ Full proportional drive joystick control
- ◇ Proportional lift/lower speed control
- ◇ Overload sensor

Power and Transmission



- ◇ 4x6V 242 Ah Deep cycle batteries
- ◇ Swing-out battery/electrical compartment doors
- ◇ 30 Ah automatic battery charger
- ◇ Charger protection system
- ◇ Dual motor direct hydraulic front wheel drive (Hyd Drive)
- ◇ Dual motor direct electric front wheel drive (E-Drive)
- ◇ 2WD
- ◇ Dual rear wheel automatic hydraulic brakes (Hyd Drive)
- ◇ Automatic front wheel brake (E-Drive)
- ◇ Emergency brake release

Functional Equipment & Accessories

- ◇ Automatic pothole protection system
- ◇ Emergency lowering system
- ◇ On-board diagnostic system
- ◇ Battery level indicator
- ◇ Hour meter
- ◇ Lubrication free scissor arm bushing
- ◇ Scissor maintenance bar
- ◇ Cylinder holding valve
- ◇ Horn
- ◇ Non-marking solid tyres
- ◇ Slope motion cut out
- ◇ All motion alarm
- ◇ Descent alarm
- ◇ Tie down lugs
- ◇ Forklift pockets
- ◇ Tilt level sensor with audible alarm
- ◇ AC Power on the platform

Optional Accessories

- ◇ Airline to platform
- ◇ Platform work lights
- ◇ Custom paint
- ◇ Lithium battery



Model	MPD.9308 Hydraulic Drive	MPD.9308E Electric Drive
Dimensions		
A – Working Height	9,30 m	9,30 m
B – Platform Height - Lifted	7,30 m	7,30 m
D– Platform Height - Lowered	1,32 m	1,32 m
D+C– Closed Height - Stowed handrails	2,46 m	2,46 m
Closed Height - Handrails folded	1,95 m	1,95 m
C– Handrails Height	1,10 m	1,10 m
ExF – Platform Dimensions	1,75 x 0,80 m	1,75 x 0,80 m
K- Extension Deck	0,70 m	0,70 m
G– Total Width	0,80 m	0,80 m
L– Total Length	1,93 m	1,93 m
J- Wheelbase	1,46 m	1,46 m
Ground Clearance - Center	10 cm	10 cm
Ground Clearance pothole deployed	25 mm	25 mm
Performance		
Lift Capacity	300 kg	300 kg
Extension Deck Capacity	100 kg	100 kg
Maximum Occupancy	2	2
Rise / Lower Time	40 / 48 sec	40 / 48 sec
Weight	1750 kg	1750 kg
Gradeability	%25	%25
Drive Speed (Rised / Stowed)	0,8 / 2,4 km	0,8 / 2,4 km
Tyres - Solid non-marking	12x4,5	12x4,5
Turning Radius	1600 mm	1600 mm
Drive Type	Front Wheel-Hydraulic	Front Wheel-Electric
Brake	Rear Wheel - Hydraulic	Front Wheel-Electric
Power		
Power Source	24 V Battery	24 V Battery
Battery	4x6V 242 Ah	4x6V 242 Ah
Charger	24V 30 Ah	24V 30 Ah